

## Viking 40E Static Jacketed Kettle

Model – Viking 40E (4215340)

### FEATURES

- Viking static jacketed kettle with lid
- Electric heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories



### TECHNICAL DATA

Net Volume 40L

Spare Volume 8 L

Gross Volume 48 L

Dimensions

Width 1047mm

Height 1039mm

Depth 743mm

Connections

Water Cold ø15mm

Hot ø10mm

Electrical

Power 9 kW

Voltage 400-415V,

3P+N+E 50/60Hz

AMP 16A

Total Heat

9kW

Load

Latent 0.4 kW,

Sensible 1.9 kW

Waste

By kitchen

contractor

Net Weight

155 kg


NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215837

Single kettle subsurface – 4215838

Group kettle surface – 4215845

Group kettle subsurface - 4215846



Finland

[metos.com/manufacturing](http://metos.com/manufacturing)

Metos Oy Ab

Ahjonkaarre

FI 04220 Kerava

Finland

Telephone +358 204 3913

[international.sales@metos.com](mailto:international.sales@metos.com)

(1) Electrical connection

(2) Cold water connection

(3) Hot water connection

(4) Data cable (HACCP option)

(5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	T mm	D mm	N mm	V mm
40E	1047	897	900	630	730	1710	400	730	455	613

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.