

Viking 100S Static Jacketed Kettle

Model – Viking 100S (4215534C)

FEATURES

- Viking static jacketed kettle with lid
- Steam heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories




TECHNICAL DATA

Net Volume	100L	Electrical	Power 0,3 kW
Spare Volume	10.5 L		Voltage 230V,
Gross Volume	110.5 L		1P+N+E 50/60Hz
Dimensions			AMP 16A
Width	1154mm	Total Heat	16kW
Height	1039mm	Load	Latent 0.8 kW,
Depth	792mm		Sensible 3.4 kW
Connections		Waste	By kitchen
Water	Cold ø15mm		contractor
	Hot ø10mm	Net Weight	185 kg
		Steam cons	30kg/hr

NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215837
Single kettle subsurface – 4215838
Group kettle surface – 4215845
Group kettle subsurface - 4215846



Finland
metos.com/manufacturing

Metos Oy Ab
Ahjonkaarre
FI 04220 Kerava
Finland
Telephone +358 204 3913
international.sales@metos.com

- (1) Electrical connection
- (2) Cold water connection
- (3) Hot water connection
- (4) Data cable (HACCP option)
- (5) Control cables to building for heating control of kettle
- (6) Steam connection
- (7) Steam condensate outlet

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	T mm	D mm	N mm	V mm
100S	1154	1004	1080	710	850	1800	500	785	405	720

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.