

## Viking 300E Static Jacketed Kettle

Model – Viking 300E (4215850)

### FEATURES

- Viking static jacketed kettle with hinged lid
- Electric heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Hydraulic tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories



### TECHNICAL DATA

Net Volume 300L

Spare Volume 33 L

Gross Volume 333 L

Dimensions

Width 1560mm

Height 1039mm

Depth 1161mm

Connections

Water Cold ø15mm

Hot ø10mm

Electrical

Power 40 kW

Voltage 400-415V,

3P+N+E 50/60Hz

AMP 63A

Total Heat

40kW

Load

Latent 1.9 kW,

Sensible 9.6 kW

Waste

By kitchen

contractor

Net Weight

420 kg




**NOTE - Mandatory installation kit required for all installations, options are:**

Single kettle surface – 4215839

Single kettle subsurface – 4215840

Group kettle surface – 4215843

Group kettle subsurface - 4215844



**Finland**

[metos.com/manufacturing](http://metos.com/manufacturing)

**Metos Oy Ab**

Ahjonkaare

FI 04220 Kerava

Finland

Telephone +358 204 3913

[international.sales@metos.com](mailto:international.sales@metos.com)

(1) Electrical connection

(2) Cold water connection

(3) Hot water connection

(4) Data cable (HACCP option)

(5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	S mm	T mm	D mm	N mm	V mm
300E	1560	1410	1190	1135	1135	2100	800	600	1165	450	1126

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.