

Viking 60E Static Jacketed Kettle

Model – Viking 60E (4215341)

FEATURES

- Viking static jacketed kettle with lid
- Electric heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories



TECHNICAL DATA

Net Volume 60L

Spare Volume 8 L

Gross Volume 68 L

Dimensions

Width 1047mm

Height 1039mm

Depth 743mm

Connections

Water Cold ø15mm

Hot ø10mm

Electrical

Power 10.5 kW

Voltage 400-415V,

3P+N+E 50/60Hz

AMP 16A

Total Heat

Load 10.5kW

Latent 0.6 kW,

Sensible 2.6 kW

Waste

By kitchen

contractor

Net Weight

165 kg


NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215837

Single kettle subsurface – 4215838

Group kettle surface – 4215845

Group kettle subsurface - 4215846



Finland
metos.com/manufacturing

Metos Oy Ab
Ahjonkaare
FI 04220 Kerava
Finland
Telephone +358 204 3913
international.sales@metos.com

- (1) Electrical connection
- (2) Cold water connection
- (3) Hot water connection
- (4) Data cable (HACCP option)
- (5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	T mm	D mm	N mm	V mm
60E	1047	897	1040	630	820	1710	400	730	455	613

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.