

Viking 300S Static Jacketed Kettle

Model – Viking 300S (4215522C)

FEATURES

- Viking static jacketed kettle with hinged lid
- Direct Steam heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Hydraulic tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories






TECHNICAL DATA

Net Volume	300L	Electrical	Power 0,5 kW
Spare Volume	33 L		Voltage 400V,
Gross Volume	333 L		3P+N+E 50/60Hz
Dimensions			AMP 16A
Width	1560mm	Total Heat	40kW
Height	1039mm	Load	Latent 1.9 kW,
Depth	1161mm		Sensible 9.6 kW
Connections		Waste	By kitchen
Water	Cold ø15mm		contractor
	Hot ø10mm	Net Weight	420 kg
		Steam cons	90 kg/hr

NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215839
Single kettle subsurface – 4215840
Group kettle surface – 4215843
Group kettle subsurface - 4215844



Finland
metos.com/manufacturing

Metos Oy Ab
Ahjonkaare
FI 04220 Kerava
Finland
Telephone +358 204 3913
international.sales@metos.com

- (1) Electrical connection
(2) Cold water connection
(3) Hot water connection
(4) Data cable (HACCP option)
(5) Control cables to building for heating control of kettle
(6) Steam connection
(7) Steam condensate outlet

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	S mm	T mm	D mm	N mm	V mm
300S	1560	1410	1190	1135	1135	2100	800	600	1165	450	1126

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.