

Viking 150E Static Jacketed Kettle

Model – Viking 150E (4215345)

FEATURES

- Viking static jacketed kettle with hinged lid
- Electric heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories



TECHNICAL DATA

Net Volume 150L

Spare Volume 19 L

Gross Volume 169 L

Dimensions

Width 1360mm

Height 1039mm

Depth 965mm

Connections

Water Cold ø15mm

Hot ø10mm

Electrical

Power 20 kW

Voltage 400-415V,

3P+N+E 50/60Hz

AMP 32A

Total Heat

20kW

Load

Latent 1.0 kW,

Sensible 4.3 kW

Waste

By kitchen

contractor

Net Weight

250 kg


NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215839

Single kettle subsurface – 4215840

Group kettle surface – 4215843

Group kettle subsurface - 4215844



Finland

metos.com/manufacturing

Metos Oy Ab

Ahjonkaarre

FI 04220 Kerava

Finland

Telephone +358 204 3913

international.sales@metos.com

(1) Electrical connection

(2) Cold water connection

(3) Hot water connection

(4) Data cable (HACCP option)

(5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	S mm	T mm	D mm	N mm	V mm
150E	1360	1210	1010	895	910	1980	800	600	945	420	926

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.