

## Viking 200S Static Jacketed Kettle

Model – Viking 200S (4215537C)

### FEATURES

- Viking static jacketed kettle with hinged lid
- Steam heated version
- 316 Stainless steel bowl
- Electromechanical controls
- Step-less temperature control
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories



### TECHNICAL DATA

Net Volume 200L

Spare Volume 19 L

Gross Volume 219 L

Dimensions

Width 1360mm

Height 1039mm

Depth 965mm

Connections

Water Cold ø15mm

Hot ø10mm

Electrical

Power 0,3 kW

Voltage 230V,

1P+N+E 50/60Hz

AMP 16 A

Total Heat

30kW

Load

Latent 1.4 kW,

Sensible 6.1 kW

Waste

By kitchen contractor

Net Weight

270 kg

Steam cons

60 Kg / hr




NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215839

Single kettle subsurface – 4215840

Group kettle surface – 4215843

Group kettle subsurface - 4215844



Finland

[metos.com/manufacturing](http://metos.com/manufacturing)

Metos Oy Ab

Ahjonkaarre

FI 04220 Kerava

Finland

Telephone +358 204 3913

[international.sales@metos.com](mailto:international.sales@metos.com)

- (1) Electrical connection
- (2) Cold water connection
- (3) Hot water connection
- (4) Data cable (HACCP option)
- (5) Control cables to building for heating control of kettle
- (6) Steam connection
- (7) Steam condensate outlet

| Model | L1<br>mm | L2<br>mm | M<br>mm | L<br>mm | LM<br>mm | H<br>mm | S<br>mm | T<br>mm | D<br>mm | N<br>mm | V<br>mm |
|-------|----------|----------|---------|---------|----------|---------|---------|---------|---------|---------|---------|
| 200S  | 1360     | 1210     | 1130    | 895     | 980      | 1980    | 800     | 600     | 945     | 420     | 926     |

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.