Viking 200E Combi Jacketed Kettle

Model – Viking Combi 200E (4215944C)

FEATURES

- Viking kettle with mixer
- Electric heated version
- 316 Stainless steel mixing bowl
- Electromechanical controls
- Safety grid lid (standard)
- Stepless temperature control
- Multi-function mixing tool
- 2 mixing programs
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories

TECHNICAL DATA

Net Volume	200L
Spare Volume	19 L
Gross Volume	219 L
Dimensions	
Width	1360mm
Height	1039mm
Depth	965mm
Connections	
Water	Cold ø15mm Hot ø10mm

Electrical	Power 31.5 kW Voltage 400-415V, 3P+N+E 50/60Hz AMP 63A
Total Heat Load	30kW Latent 1.4kW, Sensible 6.1 kW
Waste	By kitchen contractor
Net Weight	270 kg

NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215839
Single kettle subsurface – 4215840
Group kettle surface – 4215843
Group kettle subsurface - 4215844

Finland
metos.com/manufacturing

Metos Oy Ab
Ahjonkaarre
FI 04220 Kerava
Finland
Telephone +358 204 3913
international.sales@metos.com

(1) Electrical connection
(2) Cold water connection
(3) Hot water connection
(4) Data cable (HACCP option)
(5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	S mm	T mm	D mm	N mm	V mm
200E	1360	1210	1130	895	980	1980	800	600	945	420	926

Disclaimer: All unit capacities are based on subjective testing.
In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.

© Copyright Metos Oy Ab