Viking 60E Combi Jacketed Kettle

Model – Viking Combi 60E (4215940C)

FEATURES

- Viking kettle with mixer
- Electric heated version
- 316 Stainless steel mixing bowl
- Electromechanical controls
- Safety grid lid (standard)
- Stepless temperature control
- Multi-function mixing tool
- 2 mixing programs
- Electric tilting
- Measuring stick
- Water faucet (cold water)
- Hand shower (option)
- Strainer plate (option)

Please refer to Metos website for options and accessories

TECHNICAL DATA

Net Volume	60L
Spare Volume	8 L
Gross Volume	68 L
Dimensions	
Width	1047mm
Height	1039mm
Depth	743mm
Connections	
Water	Cold ø15mm Hot ø10mm

Electrical	Power 11.25 kW Voltage 400-415V, 3P+N+E 50/60Hz AMP 25A
Total Heat Load	10.5kW Latent 0.6kW, Sensible 2.6 kW
Waste	By kitchen contractor
Net Weight	165 kg

NOTE - Mandatory installation kit required for all installations, options are:

Single kettle surface – 4215837
Single kettle subsurface – 4215838
Group kettle surface – 4215845
Group kettle subsurface - 4215846

Finland
metos.com/manufacturing

Metos Oy Ab
Ahjonkaarre
FI 04220 Kerava
Finland
Telephone +358 204 3913
international.sales@metos.com

(1) Electrical connection
(2) Cold water connection
(3) Hot water connection
(4) Data cable (HACCP option)
(5) Control cables to building for heating control of kettle

Model	L1 mm	L2 mm	M mm	L mm	LM mm	H mm	T mm	D mm	N mm	V mm
60E	1047	897	1040	630	820	1710	400	730	455	613

Disclaimer: All unit capacities are based on subjective testing.
In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.

© Copyright Metos Oy Ab