


- Ⓐ Lead-through holes: The drain tube and the electric cable can be led from either side of the machine
- ① Electric supply: semi-fixed, cable length 2,5m, cable diameter Ø15mm
- ② Hot water connection: 3/4", water pressure 200 - 400kPa
- ③ Drain: tube length 1,2m, Ø24 mm, drain flow 3l/s, Floor drain underneath the machine is not allowed due to the rising steam and vapors

Code	Electric supply	P/kW	Fuse/A
4246470MM	3/PE AC 440V 60Hz	10,5	16
4246470MK	3/PE AC 400V 50Hz	10,5	16

Vers.	Muutos:	Pvm.	Suun.
Tämä piirustus on Metos Oy Ab:n omaisuutta, kopiointi tai osittainenkin jäljentäminen ilman Metos Oy Ab:n lupaa on ehdottomasti kielletty. This document may not be copied in part or in whole by any process nor passed on to a third party without the written permission of the owner Metos Oy Ab.			
Suun.	www.metos.com	Kaupalliset asiat:	Työmaa-asiat:
Suhde:	1: 25 A4	Proj.no	Tarj./lauseke. Pvm. 13.08.2020
		Nimitys Dishwasher HOOD 130 LUX2 DDE	
		Piiir.no	
Metos Oy Ab FI-04220 KERAVA Tel: 0204 39 13 Fax: 0204 39 4432		Lehti	