



HEATING ELEMENTS

Type	T9	T9	T11	T13/T16	T16	T24	T24/T35	T35
kW/Max	9	12	13	18	24	30	36	48
W1	3x1,5kW	3x2kW	3x1,5kW	3x2kW	3x2kW	3x1,5kW	3x2kW	3x2kW
W2	3x1,5kW	3x2kW	3x1,5kW	3x2kW	3x2kW	3x1,5kW	3x2kW	3x2kW
W3	-	-	2x2kW 1x2,15kW	3x2kW	3x2kW	3x2kW	3x2kW	3x2kW
W4	-	-	2x1,5kW 1x2,15kW	3x2kW	3x2kW	3x2kW	3x2kW	3x2kW
W5	-	-	-	3x1,5kW	3x2kW	3x2kW	3x2kW	3x2kW
W6	-	-	-	-	3x1,5kW	3x2kW	3x2kW	3x2kW
W7	-	-	-	-	3x1,5kW	3x2kW	3x2kW	3x2kW
W8	-	-	-	-	-	3x2kW	3x2kW	3x2kW

ELECTRICAL HEATING

Machine types where used		Tolerance		Ra		Scale:	
T-Dryers:						Material:	
480V						Rough dimensions:	
50/60Hz						Standard for rough material:	
Date	Author	Date	Author	Electrical power diagram			
	30may12		Pst				
	Releas.						
Modification		Date		Name/Proj.		Replaces:	
X						960	
						528 500	
						Page: 1	
						Pages: 1	